



Ontinental → DAMPF TRIX® 6000 OIL - DAMPF / STEAM - PN 18 BAR

**LABEL:** 1 red and 2 white coloured axial markings on black cover "Continental DAMPF TRIX® 6000 OIL - DAMPF / STEAM - PN 18 BAR / 261 PSI -  $\Omega$  Ölkanne Made in Germanv"

#### **APPLICATIONS**

Construction industry, Machinery and plant engineering, Refineries, Shipping industry

## **FLOW MEDIUM**

Hot water, Steam, Water

### STANDARD / APPROVAL

DIN EN ISO

### **DESCRIPTION**

**Inner lining:** EPDM, black, non-porous, smooth **Reinforcements:** 2 galvanized reinforcements

**Cover:** Spezial elastomer, black, fabric patterned, abrasion resistant, resistant

to oil and fats, resistant to ozone, weather and UV

Working 18 bar / 261 psi

pressure up to:

**Temperature** up to +120  $^{\circ}$ C / +248  $^{\circ}$ F

range: Further

Burst pressure > 180 bar / 2.611 psi, safety factor 10:1

properties:

Electrically conductive, R <  $10^6 \,\Omega$ /line Improved resistance against pop corning

Temperature range for saturated steam up to max. +210°C / +410°F, short term +220°C / +428°F at 23 bar / 333 psi (saturated steam)

# **TECHNICAL DATA**

nominal width zoll/inch	inner-Ø mm	wall thickness mm	<b>outer-Ø</b> mm	<b>length</b> m	working pressure		min. burst pressure		min. bending radius	weight
					bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/2	13	6	25	40	18	261	180	2611	130	530
3/4	19	7	33	40	18	261	180	2611	190	900
1	25	7.5	40	40	18	261	180	2611	250	1200
1 1/4	32	8	48	40	18	261	180	2611	320	1550
1 1/2	38	8	54	40	18	261	180	2611	380	1800
2	50	9	68	40	18	261	180	2611	500	2600

Attention: Superheated steam will reduce the durability considerably