



## CONTI® ULTIMATE GASKET

For hydraulic and pneumatic transport of abrasive media



### APPLICATIONS

Chemical industry, Foundries, Gravel plants, Gravel works, Hydraulic and pneumatic applications, Mining industry, Powerplants, Sewage Treatment Plants

### DESCRIPTION

**Further properties:** Compatible with CONTI® ULTIMATE, CONTI® ULTIMATE CONDUCTIVE and CONTI® ULTIMATE Flange

Conical shape ensures ease of installation

Reliable sealing of the hose end face, the strength member is protected from the abrasive pumped medium

Rubber sealing with steel reinforcement

Sealing thickness: 8 mm

Secure connection between hose and flange

### TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm
2	51
2 1/2	63
3	76
3 1/2	90
4	102
5	127
6	152
8	204
10	254
12	305
14	355
16	405
18	455
20	508
24	610

#### Industrial Fluid Solutions

ContiTech Schlauch GmbH  
Continentalstr. 3-5 | 34497 Korbach, Germany  
[industrialhoses@fluid.contitech.de](mailto:industrialhoses@fluid.contitech.de)

Version: 2021\_04.57 | 2021-05-10

#### [www.continental-industry.com](http://www.continental-industry.com)

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2021 ContiTech AG. All rights reserved. For complete information go to: [www.continental-industry.com/en/special-pages/disclaimer-publications](http://www.continental-industry.com/en/special-pages/disclaimer-publications)