



CONTI® ULTIMATE - FLANGE

For hydraulic and pneumatic transport of abrasive media



LABEL: CONTI® ULTIMATE DN 51

APPLICATIONS

Chemical industry, Foundries, Gravel plants, Gravel works,
Hydraulic and pneumatic applications, Mining industry,
Powerplants, Sewage Treatment Plants

DESCRIPTION

Working pressure up to: 10 bar / 145 psi

Further properties: Compatible with CONTI® ULTIMATE, CONTI® ULTIMATE CONDUCTIVE and CONTI® ULTIMATE gasket
Made of high-strength aluminium alloy
Non-corrosive
Robust
Sea water resistant
Suitable for both DIN EN 1092-1 (PN 10) / ANSI 16.5B (150lbs) standards

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	working pressure		weight aprx. g/ Stck
		bar	psi	
2	51	10	145	1400
2 1/2	63	10	145	3400
3	76	10	145	2300
3 1/2	90	10	145	3800
4	102	10	145	3900
5	127	10	145	6900
6	152	10	145	7800
8	204	10	145	12700
10	254	5	73	13100
12	305	5	73	21800
14	355	5	73	26400
16	405	5	73	38100
18	455	5	73	42000
20	508	5	73	73100
24	610	5	73	90000

Pressure based on room temperature / Inch dimensions according to ANSI 16.5B, metric dimensions according to DIN EN 1092-1

Industrial Fluid Solutions

ContiTech Schlauch GmbH
Continentalstr. 3-5 | 34497 Korbach, Germany
industrialhoses@fluid.contitech.de

Version: 2021 04.100 | 2021-05-10

www.continental-industry.com

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2021 ContiTech AG. All rights reserved. For complete information go to: www.continental-industry.com/en/special-pages/disclaimer-publications