

Eagle EPDM Steam Hose



High Pressure Steam Hose

- Application:** High pressure steam hose for saturated steam, used in closed steam systems in heating and cleaning applications, drain after use, also suitable for high pressure air and water applications
- Tube:** EPDM High temperature and steam resistant, black, smooth
- Reinforcement:** Steel wire braided
- Cover:** EPDM Red, high temperature, weather and ozone resistant, smooth with cloth impression, pin pricked
- Temperature:** -31°F to +410°F
- Branding:** EAGLE EPDM STEAM
- Standard Length:** 100 feet
- Packaging:** Coils with PE Wrapping
- Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	Bend Radius	WP	Burst	Weight
	in	in	in	psi	psi	lbs/ft
010-0081-0250I	1/2	0.98	2.56	261	2611	2.1
010-0121-0250I	3/4	1.26	3.74	261	2611	3.8
010-0161-0250I	1	1.50	4.92	261	2611	4.4
010-0201-0250I	1-1/4	1.81	6.30	261	2611	6.2
010-0241-0250I	1-1/2	2.05	7.48	261	2611	6.7
010-0321-0250I	2	2.64	10.03	261	2611	10.0



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com