

# Eagle OILFLEX

## 150 PSI Tank Truck Hose



**Application:** Suction and discharge application in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

**Tube:** Black conductive, oil resistant Nitrile (NBR)

**Reinforcement:** High tensile textile cord, double steel helix

**Cover:** Red corrugated - abrasion, hydrocarbon and ozone resistant

**Temperature:** -40°F to +180°F

**Branding:** EAGLE OILFLEX 150 PSI WP

**Couplings:** Contact JGB for proper fitting recommendation and coupling procedure

Part #	ID	OD	Bend Radius	WP	Weight
	in	in	in	psi	lbs/ft
009-0243-0150I	1-1/2	1.97	3	150	0.74
009-0323-0150I	2	2.52	3	150	1.06
009-0483-0150I	3	3.54	4	150	1.85
009-0643-0150I	4	4.65	6	150	2.60
009-0963-0150I	6	6.77	18	150	6.00
009-1283-0150I	8	8.86	25	150	9.00

\* Full Vacuum



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

**New England Region**  
Liverpool, NY 13088  
(315) 451-2770

**Great Lakes Region**  
Cheektowaga, NY 14225  
(716) 684-8224

**Mid-Atlantic Region**  
Charlotte, NC 28273  
(704) 588-9920

**Midwest Region**  
St. Louis, MO 63111  
(314) 256-0833

**Gulf Coast Region**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)