

J-FLEX® 10K Jack Hose

Hydraulic

Hydraulic Jack Hose



Application: Designed for hydraulic hack applications

Tube: Oil resistant synthetic rubber

Reinforcement: Two braids of high tensile steel wire.

Cover: MSHA, abrasion and weather resistant synthetic rubber

Temperature: -40°F to +212°F depending on the medium

Branding: J-FLEX® 10K JACK HOSE 10,000PSI WP / 20,000PSI BP MSHA

Couplings: Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	Bend Radius	Max WP	Test Pressure	Burst Pressure	Weight
	in	in	in	psi	psi	psi	lbs/ft
172-8004-1000I	1/4	0.59	4	10,000	12,000	20,000	0.20
172-8006-1000I	3/8	0.75	5	10,000	12,000	20,000	0.34

3/8" J-FLEX 10K JACK HOSE 10,000 PSI WP / 20,000 PSI BP MSHA IC-8/17



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com