

Eagle Water Discharge 150 PSI

Medium Duty Water Discharge



Application: Water discharge applications in construction, industry, and agriculture.

Tube: Synthetic rubber

Reinforcement: High-tensile synthetic textile

Cover: Weather and ozone resistant synthetic rubber

Temperature: -13°F to +158°F

Branding: EAGLE WATER DISCHARGE 150 PSI WP

Couplings: Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	WP	Min Burst	Weight	Length
	in	in	psi	psi	lbs/ft	ft
005-0242-0150I	1.50	1.85	150	450	0.60	100
005-0322-0150I	2.00	2.36	150	450	0.80	100
005-0402-0150I	2.50	2.91	150	450	1.12	100
005-0482-0150I	3.00	3.46	150	450	1.47	100
005-0642-0150I	4.00	4.53	150	450	2.21	100
005-0962-0150I	6.00	6.50	150	450	3.07	100
005-1282-0150I	8.00	8.74	150	450	5.45	100
005-1602-0150I	10.00	10.63	150	450	7.17	100



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com